

COVERMATT DRYWALL PRIMER

Crown Trade Covermatt Drywall Primer has been developed to even out surface porosity on dry lined walls and ceilings. It can also be used as a mist coat for new plaster where access to water is difficult. Crown Trade Covermatt Drywall Primer provides the perfect base for first decoration products.

AVAILABILITY

Colour Range	White.
Packaging	10 litres.

PROPERTIES

Drying Time	Under normal drying conditions touch dry in 1-2 hours, recoatable after 4 hours. Allow for adequate ventilation during the drying period.
Finish	Matt.
Composition	Pigment: Titanium Dioxide and extenders. Binder: Acrylic polymers. Solvent: Water.
Spreading Rate	Up to 15m ² per litre dependant on surface texture and porosity.
Wet Film Thickness	67 micrometres at 15m ² per litre
Dry Film Thickness	10 micrometres at 15m ² per litre.
Volume Solids	15%.
Flash Point	Not applicable.
VOC Content	EU limit value for this product (cat.A/a): 75 g/l (2007) / 30g/l (2010) This product contains max. 29 g/l VOC
Limitations	For interior use only. Do not apply when air or substrate temperatures are likely to fall below 8°C or when the relative humidity is above 80% during application or the drying period.

PREPARATION

New Surfaces	All surfaces must be sound, clean, suitably dry and free from anything that will interfere with the adhesion of the materials to be applied.
--------------	--

COATING SYSTEM

Apply one coat. Allow to dry before applying the chosen finishing coats.

APPLICATION

Stir well before use. Apply undiluted, by brush, roller or spray.

CLEANING

Return surplus material to container. Wash with clean water immediately after use.

HEALTH AND SAFETY

Please refer to the Safety, Health and Environmental Information on the container. Take special precautions during the surface preparation of pre 1960's painted surfaces as they may contain harmful lead. For further information contact the Crown Trade Customer Relations Team. When preparing all surfaces avoid the inhalation of dust and/or metal particles. Wear a suitable facemask. Material Safety Data Sheets for this and all other Crown Paints products are freely available from the place of purchase or the address below. Store in secure dry conditions inaccessible to children or animals. Containers should be kept closed during storage. Do not empty into drains, watercourses or access routes to septic tanks.

GENERAL INFORMATION

Apply all products in accordance with BS 6150: 2006 Code of practice for painting of buildings and BS 8000: Part 12: 1989 Code of practice for decorative wallcoverings and painting. Under normal and frost free conditions this product will remain usable for up to two years if stored correctly and unopened.

Every care is taken to ensure that all information provided on this Technical Data Sheet is accurate. Crown Paints is unable to guarantee results as it has no control over the conditions under which its products are applied.

Before using this product please ensure you have the latest information. For help or more information contact the Crown Trade Customer Relations Team on:

Tel: 0845 389 9583

Fax: 0845 389 9584

e-mail: info@crowntrade.co.uk

website: www.crowntrade.co.uk

Crown Trade and the Crown Trade logo are trade marks of Crown Brands Limited.

This information is correct at date of issue October 2011.



P O Box 37, Crown House, Hollins Road, Darwen, Lancashire, BB3 0BG

Tel: 01254 704951 Fax: 01254 870155

Email: info@crowntrade.co.uk

Website: www.crowntrade.co.uk