

**DOES
EXACTLY
WHAT IT
SAYS ON
THE TIN***

Ronseal Promise, if you do exactly what it says on the tin, this product will do exactly what it says on the tin.

The ultimate paint protection with slip resistant finish.

Ronseal Diamond Hard Doorstep Paint

Ronseal uses advanced acrylic technology that delivers the ultimate paint protection for all brick, stone and concrete doorsteps. Ronseal's unique Diamond Hard formula not only resists knocks, scuffs and scratches, but also offers slip resistance for a safer finish*.

Advanced technology: The advanced formula doesn't require a separate primer and adheres superbly. It provides a long lasting, smooth and quick drying finish that will resist flaking, peeling and chipping, maintaining its appearance for longer.

Usage Areas	Use on brick, stone and concrete doorsteps.
Compatibility	Not suitable for use over ceramic tiles.
Coverage	Up to 9m ² per 750ml, enough for 2 coats on 3 doorsteps measuring 1m x 300mm.
Dry Times	Touch dry in 1-2 hours. Overcoatable in 4-6 hours.
Clean Up	Brushes wash out in water and detergent.

Preparation

Surfaces should be clean, dry and free from dust, dirt and grease. If mould or moss is present, treat with a suitable proprietary disinfectant. Scrub the surface with a stiff brush using water and detergent and allow to dry thoroughly. Ensure all loose materials are removed. It is not recommended to apply this product in damp conditions or if temperature is below 10°C. **Previously Painted Surfaces:** Thoroughly wire brush to remove any loose or flaking paint. Sand down and wipe clean with white spirit to remove dust. Treat any areas of bare surface as above.

Application & Clean Up

Stir the paint thoroughly before use. Apply by brush or pad. When using more than one tin, intermix before use to ensure an even colour. Apply a minimum of 2 coats, allowing 4-6 hours between coats. The paint is ready to walk on after 4-6 hours but protect from heavy traffic or water for 72 hours. Remove as much paint as possible from application equipment before cleaning. Clean brushes with water and detergent. Avoid abrasive cleaners. Some local authorities have special facilities for disposing of waste coatings. Do not empty into drains or watercourses.

* Although this product has a slip resistant additive, absolute slip resistance cannot be guaranteed.

RONSEAL DIAMOND HARD DOORSTEP PAINT

Keep out of the reach of children. Avoid contact with skin and eyes. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. After contact with skin, wash immediately with plenty of water. Use only in well-ventilated areas. Protect from frost – do not apply below 10°C or in high humidity.

WISE PRECAUTIONS

Always read the instructions carefully before use. To avoid the risk of spillage always store and transport in a secure and upright position.

EU limit value for this product (cat A/i): 140g/l (2007)/ 140g/l (2010). This product contains max 85g/l VOC.

**For further advice please contact:
Ronseal Technical Services,
Tel: 0114 240 9469**

Ronseal Ltd., Chapeltown,
Sheffield S35 2YP
Tel: 0114 246 7171,
Fax: 0114 245 5629
E-mail: enquiry@ronseal.co.uk
www.ronseal.co.uk

Ronseal and Ronseal Does Exactly What It Says on the Tin are registered trademarks of The Sherwin-Williams Company. © 2010

750ml e

