

**BLACKFRIAR PAINTS LTD**  
**TECHNICAL DATA SHEET**  
BF072 **Blackfriar French Polish.**

Revision
Date:
12/11/13

<b><u>Product Information</u></b>	<b><u>Technical Specification</u></b>	<b><u>Recommended Spreading Rate</u></b>
<p><b><u>Description</u></b></p> <p>A traditional high gloss French polish.</p> <p><b><u>Usage/purpose</u></b></p> <p>For use on all new, stained or previously French polished woods especially antique furniture, tables, musical instruments etc. Can be used as a sanding sealer.</p> <p><b><u>Characteristics</u></b></p> <p>Fast drying. Gives a smooth high gloss finish that brings out the natural beauty of wood.</p> <p><b><u>Finish</u></b></p> <p>Multiple coats will provide a very smooth high gloss finish.</p> <p><b><u>Colour(s)</u></b></p> <p>Pale yellow/ brown.</p> <p><b><u>Packaging</u></b></p> <p>100ml, 200ml, 500ml. Larger sizes may be available on request dependant on volume required.</p> <p><b><u>Disclaimer;</u></b> The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. It is our recommendation that a trial area is first coated to ensure the product is satisfactory to individual requirements</p>	<p><b><u>Composition</u></b></p> <p>Based on Orange shellac and methylated spirit.</p> <p><b><u>Properties</u></b></p> <p>VOC Content: EU Limit Value (cat A/f) 700g/L This product contains max 700g/L</p> <p><b><u>Performance</u></b></p> <p>Gives a deep superb glossy appearance suitable for antiques and fine woodwork etc. Not recommended for areas of high wear and tear. For interior use only.</p> <p><b><u>Surface Preparation</u></b></p> <p>Ensure the substrate to be polished is sound and free from any surface contaminant likely to give adhesion problems (e.g. wax, grease, polish etc). Surfaces which have been previously wax polished must be degreased prior to sanding. Blackfriar Furniture Cleaner Restorer may be used to degrease surfaces.</p> <p><b><u>Application Method</u></b></p> <p>Ensure product is thoroughly shaken prior to use. Apply using a 'rubber' in a circular motion. Do not allow the rubber to dry out. Build up coats until the required finish is obtained.</p>	<p>Dependant on absorbency of the wood, approx 10-15 m<sup>2</sup> per litre.</p> <p><b><u>Thinning</u></b></p> <p>Up to 10% with Methylated Spirit.</p> <p><b><u>Drying Time</u></b></p> <p>Touch dry in 15-30 mins Recoat after 1 hour under normal conditions (20°C 50% r/h).</p> <p><b><u>Cleaning</u></b></p> <p>Clean application equipment or spills with Methylated Spirit</p> <p><b><u>Limitations</u></b></p> <p>For interior use only</p> <p><b><u>Environmental Info.</u></b></p> <p>Dangerous for the environment. <b>For Technical Enquiries, Material Safety Data Sheets</b> Telephone 0191 4113146</p> <p>Paint Product UN No. 1263.</p> <p><b>Tor Coatings Ltd.</b> <b>Portobello Industrial Est,</b> <b>Birtley</b> <b>Chester-le Street</b> <b>County Durham</b> <b>DH3 2RE</b></p>