

SATU LAUDESUOJA

protection for benches in the steam-room

PRODUCT TYPE

SATU LAUDESUOJA Protection for benches in the steam-room is a colourless and odourless protection containing paraffin oil for wooden surfaces. It forms a dirt and water repellent but breathable coat. SATU LAUDESUOJA emphasizes the natural colour of wood.

The product has been classified in Emission Classification of building materials to **Group M1**.

USAGE

Treatment of benches in the steam-rooms of saunas, wooden kitchen table tops etc. Suitable for untreated and previously oil treated wooden surfaces. Can also be used for treating wall and ceiling panels in steam-rooms.

TECHNICAL DATA**Solids**

About 100 % by volume

Volatile organic compound (VOC)

The product is not included in the EU VOC directive.

Practical spreading rate

Applied once onto a smooth surface: abt. 10 m²/l

Density

abt. 1.0 g/ml

Drying time at +23°C / 50% RH**- dust free**

after 1 h

Next treatment

after 2 h

Dry to use

the following day (see page 2: Taking into use)

Washing the equipment

Clean the equipment immediately after use with warm water and detergent.

Colours

Clear

Packages

0,25 L, 1 L

(availability varies by country)

DIRECTION FOR USE**Surface preparation**

Clean new wooden surfaces from dust and dirt.
Wash previously oiled surfaces with RENSA SAUNA sauna cleaner and rinse thoroughly with water. If the wooden surface has previously been varnished or treated with protection for sauna, the surface must be sanded bare.

Application

Before use stir the product thoroughly.
Apply SATU LAUDESUOJA with brush, sponge or clean cloth. Apply to a clean and dry wooden surface 1 to 3 times depending on the absorption properties of the surface. Wipe off excess oil 30 min after the application.

Conditions

The surface to be treated must be dry.
During the application and drying period the temperature of the ambient air, the surface and the product shall be above +10 °C and the relative air humidity below 80%.
Good ventilation during the application and drying period quickens the drying process.

Taking into use

Sauna must be preheated and ventilated before taking into use.

Surface maintenance

The surface can be cleaned by wiping with a neutral (pH 6 - 8) detergent. Detergent and dirt are removed by wiping and/or rinsing the surface with clean water. Use a cleaning cloth, soft sponge or similar for cleaning. Avoid coarse brushing or heavy abrasion. Follow the dilution and other instructions of the detergent producer when using detergents.

ADDITIONAL INFORMATION

Must be stored tightly closed and kept cool.

MUST NOT FREEZE.

The information of this data sheet is based on laboratory tests and practical experience. The figures are for guidance only and depend on, for example, colour and gloss. As we have no control over the use and application conditions, we are only responsible for the quality of the product and guarantee that it conforms to our quality control. We accept no liability for any loss or damage resulting from the application of the product contrary to the directions or the intended use. The latest versions of our data sheets, material safety data sheets and system sheets are on our home pages www.teknos.com.



EN_1912_Tuoteseloste.pdf