



DIAMOND EGGSHELL

Dulux Trade Diamond Eggshell is a tough, water-based mid-sheen emulsion paint that uses **Diamond Technology** from **Dulux Trade**, making it 10 times tougher than **Dulux Trade** Vinyl Silk and **Dulux Trade** Vinyl Matt. It also features Stain Repellent Technology, actively repelling stains that come into contact with the surface and ensuring ease of cleaning. Ideal for high traffic areas such as stairwells and hallways.

KEY BENEFITS

- Actively Repels Stains
- Superior Durability
- Repeatably Wipeable Eggshell Finish

PRODUCT INFORMATION

Typical Use

Suitable for interior use on plaster, masonry and wood. Also suitable for use in kitchens and bathrooms. Do not use externally.

Pack Size

1L, 2.5L and 5L.

Colour Range

See appropriate **Dulux Trade** colour literature or visit duluxtrade.co.uk.

Film Properties

Chemical Resistance: Not recommended.

Heat Resistance: Not recommended for use on heated surfaces, such as radiators.

Water Resistance: Resistant to the levels of atmospheric humidity present in normal interior environments and will withstand repeated washing. Suitable for use in kitchens and bathrooms. Not suitable for use on immersed surfaces or where there is heavy and prolonged condensation.

Film Thickness

Film thickness will be dependent on the coverage achieved.

Wet: 63 microns.

Dry: 23 microns.

Composition (nominal)

Pigment: Lightfast Pigments.

Binder: Acrylic Copolymer Emulsion.

Solvent: Water.

Volume Solids

White – 37% (nominal). Other colours will vary.

SURFACE PREPARATION

To get the best results with **Dulux Trade** Diamond Eggshell, make sure surfaces to be painted are sound, clean, dry (new surfaces particularly must be fully dry) and free from all defective or poorly adhering material such as dirt, grease and wax. New or bare surfaces should be primed with an appropriate **Dulux Trade** primer.

Thoroughly rub down previously painted surfaces using 'wet flattening' methods where possible, then wipe off with a damp, lint free cloth. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead.

DIAMOND EGGSHELL

Treat knots with a suitable knotting solution. Any surface defects should be filled with the appropriate **Polycell Trade Polyfilla**.

SYSTEMS INFORMATION

STIR THOROUGHLY BEFORE USE. Seal new or bare surfaces with a thinned first coat of **Dulux Trade** Diamond Eggshell (up to 1 part clean water to 10 parts paint). The normal finishing process is 2 full coats of **Dulux Trade** Diamond Eggshell, but on previously painted surfaces in good condition where similar colours are used, 1 coat may be sufficient. When applying water-based paints to surfaces previously decorated with a conventional solvent-based paint, very thorough surface preparation will be necessary.

For best colour consistency, purchase sufficient tinted paint for each job including touch-in at one time from the same source.

APPLICATION METHOD

Brush, roller, conventional spray or airless spray.

Do not use when the temperature is below 10°C.

Practical Coverage

A guide to the practical coverage which can be achieved under normal conditions is up to 16m² per litre.

Thinning

Sealing new or bare surfaces: Add up to 1 part clean water to 10 parts paint.

Normal use (not to be exceeded): Thinning is not usually required.

Conventional spray application: Add up to 1 part clean water to 5 parts paint.

Airless spray application: Thinning is not usually required.

Spray Recommendations

Conventional Spray: Satisfactory through most equipment.

Airless Spray: A typical set up for airless spray would be a minimum working pressure on paint of 133 bars (2000lb/sq in) with a spray tip size 0.38mm (15 thou) and a spray tip angle of 65°.

Drying Times

Single coat at standard thickness:

Touch Dry: Dependent on temperature and humidity.

Recoat: 4-6 hours, although will vary according to temperature and humidity (e.g. will take significantly longer in cold, damp conditions).

Cleaning Up

After use, remove as much product as possible from equipment before cleaning with water.



Issued 09/15

408

DIAMOND EGGSHELL

When this paint container is empty please ask your stockist about recycling. If you have leftover paint, please dispose of it responsibly and consider donating it to **Community RePaint**. Find out more at duluxtrade.co.uk/pp.

Do not use or store in extremes of temperature and protect from frost. To prevent spillage, please store and transport upright.

VOC

EU limit value for this product (cat.: A/a): 30g/l (2010).

Ready Mixed: This product contains max. 17g/l VOC. VOC content: Low (0.30-7.99%).

Tinted Colour: This product contains max. 22g/l VOC. VOC content: Low (0.30-7.99%).

Transportation & Storage

FURTHER SUPPORT

If you need further support, please contact the **AkzoNobel** Technical Advice Centre on [0333 222 70 70](tel:03332227070).

Always read full Health, Safety & Environmental Information on can before use.

Safety datasheet (SDS 408) is available free on request by telephoning the **AkzoNobel** Technical Advice Centre or by visiting duluxtrade.co.uk.

AkzoNobel, the AkzoNobel logo, the Flourish logo, Dulux Trade, Diamond Technology, Polycell, Polyfilla, Community RePaint and the Planet Possible logo are trademarks of the AkzoNobel group. © AkzoNobel 2014.



At Dulux Trade, we believe by working with our customers we can reduce waste and do more with the resources we have. Together we can create a better future for our planet. Join us at duluxtrade.co.uk/pp

AkzoNobel