

Microbarr Anti Bacterial Acrylic Matt

DESCRIPTION

Johnstone's Microbarr Anti Bacterial Acrylic Matt is a high performance, tough acrylic resin based interior coating, ideal for hygiene conscious environments and areas subject to frequent cleaning.

RECOMMENDED USES



Developed using Silver Ion Technology to inhibit bacteria and provide a tough, washable finish. For interior use in areas of high traffic and when hygiene protection is required.

SPECIAL PROPERTIES

Tough durable Matt formulated to assist in the fight against infections caused by harmful bacteria.

COLOUR RANGE

Brilliant White, Magnolia. Available in a range of colours via the Johnstone's tinting system.


FINISH

Matt.

VOLUME SOLID

42%.

COVERAGE



Johnstone's Microbarr Anti-Bacterial Acrylic Matt will cover approximately 12 square metres per litre depending on the nature and porosity of the surface. If more than one can of a colour is to be used in the same area, intermix before use.

DRYING TIME



Touch dry after 3-4 hours. Allow 4 hours before recoating.

TRANSPORTATION & STORAGE

To avoid the risk of spillage always store and transport in a secure upright position. **STORE AWAY FROM HEAT AND FLAME.**

THINNER

Clean water

VOC CONTENT

LOW VOC CONTENT 0.30-7.99%

VOC's (Volatile Organic Compounds) contribute to atmospheric pollution.

FILM THICKNESS

Wet: 83µm, dry: 28µm.

SIZE

5 litre.

PREPARATION

All surfaces should be sound, clean, dry and free from grease. Remove any crazed or flaking paint. Rub down sound glossy surfaces with fine waterproof abrasive paper and rinse thoroughly before applying a pre-coat of Johnstone's Acrylic Primer Undercoat. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during preparation of pre-1960's paint surfaces over wood and metal as they may contain harmful lead. For further advice contact Technical Advisory. Seal absorbent surfaces with a solution of up to 1 part water to 4 parts Anti-Bacterial Acrylic Matt. Prime bare timber and metal surfaces with an appropriate Johnstone's primer. Allow radiators to cool before painting. For additional information and free Johnstone's Trade datasheets call 01924 354000 or visit www.johnstones-paints.co.uk

APPLICATION



Stir well before use and apply by brush, roller or paint pad. When using a roller, use a medium pile synthetic type. Do not overfill the tray. Ensure roller is loaded evenly. If using a brush, load generously. Apply liberally and evenly; avoid overspreading.

CLEANING



Remove as much product as possible from equipment before cleaning. Clean immediately after use in warm soapy water and rinse thoroughly. Replace lid firmly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty waste paint into drains or watercourses.

PRECAUTIONS

- Ensure good ventilation during application and drying.
- Avoid contact with skin and eyes.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- After contact with skin, wash immediately with plenty of soap and water or a recognised skin cleaner.
- Keep out of the reach of children.

PROFESSIONAL DECORATORS

Safety data sheet available for professional user on request.



SigmaKalon DECORATIVE COATINGS UK AND IRELAND, SIGMAKALON UK LIMITED

Huddersfield Road, Birstall, Batley, West Yorkshire WF17 9XA Telephone: 01924 354000 Facsimile: 01924 354001 www.johnstones-paints.co.uk